



产品特点/ Product Features

- 工作温度-50℃-150℃
Working Temperature
- 易于安装
Easy to Install
- 耐磨性能
Abrasion Resistance
- 防尘降噪功能
Dustproof and Noise
Reduction Function

KST2565 由 PET 单丝和复丝针织而成。它具有良好的耐磨性和降噪性能。开放式的结构使其便于安装和拆卸。

KST2565 is knitted from PET monofilament and multifilament. It has good abrasion resistance and noise reduction performance. The open structure makes it easy to install and remove.

产品应用 /Applications

KST2565 广泛应用于线束、管道和软管，通讯、铁路、汽车等行业，为线束、管道提供防护。

KST2565 is widely used in communication, railway and automotive industries to provide protection for wire harnesses, pipes and hoses.

我们的工厂已通过 ISO 9001、IATF 16949、ISO 14001、ISO 45001 和 军工 GJB9001C 认证。

Our manufacturing site has been certified by ISO 9001, IATF 16949, ISO 14001, ISO 45001 and military GJB9001C.

性能参数/Performance Parameter

检测项目 Test Item	测试方法 Test Method	测试结果 Test Results
热老化测试 Heat ageing test	175℃, 336小时 175℃, 336 hours	无开裂或断裂 No cracking or fracture.
阻燃性试验 Flammability	FMVSS 302	符合要求 Pass

上述所有测试参数值均为典型值。产品测试报告请详询销售代表。

All the above test parameter values are typical values. For specific product test reports, please consult your sales representative.

产品规格/Specifications

型号 Part No.	名义直径 Nominal I.D. (mm)	厚度 Thickness (mm)	包装长度 Reel Length (m/reel)	货号 Art. No.
KST25650601	6	1.0 ± 0.2	200	PK-006
KST25650801	8	1.0 ± 0.2	100	PK-008
KST25651001	10	1.0 ± 0.2	100	PK-010
KST25651301	13	1.0 ± 0.2	100	PK-013
KST25651601	16	1.0 ± 0.2	50	PK-016
KST25651901	19	1.0 ± 0.2	50	PK-019
KST25652501	25	1.0 ± 0.2	50	PK-025
KST25652901	29	1.0 ± 0.2	25	PK-029
KST25653201	32	1.0 ± 0.2	25	PK-032
KST25653801	38	1.0 ± 0.2	25	PK-038
KST25654501	45	1.0 ± 0.2	25	PK-050

*可根据要求裁切固定长度/It can be cut to a fixed length as required.

*可根据要求订做其它尺寸/Other sizes can be customized upon request.

RoHS
COMPLIANT

MXTECH
Sleeving Products

Suzhou Mingxin Electronic Technology Co., Ltd.

1435 Huguang Road, Zhangpu Town, Kunshan City, Suzhou, Jiangsu Province, China. 215321

<https://petsleeving.en.alibaba.com> | <https://szmingxin.en.made-in-china.com>

TEL:0512-57305228 FAX:0512-57558111