



产品特点/ Product Features

- 工作温度-40℃~150℃
Working Temperature
- 柔软易弯折
Soft and Flexible
- 卓越的防尘性能
Excellent Dust Prevention
- 优异的耐磨性
Superior Wear Resistance
- 易于拆卸和维护
Easy to Disassemble and Maintain

TS2563 采用高强度环保尼龙长丝制成。具有良好的耐磨性和防尘功能，为软管、电缆和线束提供卓越的抗磨损保护。魔术贴开合设计，实现快速安装拆装。

TS2563 is made of high-strength environmentally friendly nylon filaments. It has good wear resistance and dustproof function, and provides excellent wear protection for hoses, cables and wiring harnesses. Velcro opening and closing design, to achieve rapid installation and disassembly.

产品应用/Applications

TS2563 适用于线束、管道、电缆组件、流体输送管线。

TS2563 is suitable for wiring harnesses, pipelines, cable assemblies, and fluid delivery pipelines.

我们的工厂已通过 ISO 9001、IATF 16949、ISO 14001、ISO 45001 和 军工 GJB9001C 认证。

Our manufacturing site has been certified by ISO 9001, IATF 16949, ISO 14001, ISO 45001 and military GJB9001C.

性能参数/Performance Parameter

检测项目 Test Items	测试方法 Test Method	测试结果 Test Results
热老化测试 Heat ageing test	150℃, 240小时 150℃, 240hours	无破损 Undamaged
低温柔韧性 Low-temperature flexibility	-40℃, 4小时 -40° C, 4 hours	符合 Pass

上述所有测试参数值均为典型值。产品测试报告请详询销售代表。

All the above test parameter values are typical values. For specific product test reports, please consult your sales representative.

产品规格/Specifications

型号 Part No.	名义直径 Nominal I.D. (mm)	展开宽度 Flat Width (mm)	壁厚 Thickness (mm)	包装长度 Reel Length (m/reel)
TS25631301	13	68 ± 4	1.1 ± 0.2	100
TS25631601	16	78 ± 4		100
TS25631901	19	90 ± 4		100
TS25632501	25	110 ± 5		100
TS25633201	32	129 ± 5		100
TS25633801	38	145 ± 6		100
TS25634501	45	168 ± 6		100

*可根据要求裁切固定长度/It can be cut to a fixed length as required.

*可根据要求订做其它尺寸/Other sizes can be customized upon request.

RoHS
COMPLIANT

MXTech
Sleeving Products

Suzhou Mingxin Electronic Technology Co., Ltd.

1435 Huguang Road, Zhangpu Town, Kunshan City, Suzhou, Jiangsu Province, China. 215321

<https://petsleeving.en.alibaba.com> | <https://szmingxin.en.made-in-china.com>

TEL:0512-57305228 FAX:0512-57558111