



产品特点/ Product Features

- 工作温度-50℃~150℃
Working Temperature
- 高扩展性
High Expandability
- 卓越阻燃性
Excellent Flame Retardancy
- 出色的耐磨性
Excellent Abrasion Resistance
- 多种颜色可选
Variety of Colors Available
- 热切端口平整
Clean Hot Cut Edges

EX600 由高品质 PET 单丝编织而成。具有可扩展性，便于套入连接器和长距离线束。具备优异的耐磨性、耐化学腐蚀性。提供多种颜色，热切端口平整。

EX600 is braided from high quality PET monofilament. Expandable for easy snapping into connectors and long distance harnesses. Excellent abrasion and chemical resistance. Available in a variety of colors with flat hot cut ports.

产品应用/Applications

EX600 适用于保护发动机舱内汽车软管，管道及电缆，使其免受磨损。

EX600 is suitable for protecting automotive hoses, pipes and cables in the engine compartment from abrasion.

我们的工厂已通过 ISO 9001、IATF 16949、ISO 14001、ISO 45001 和 军工 GJB9001C 认证。

Our manufacturing site has been certified by ISO 9001, IATF 16949, ISO 14001, ISO 45001 and military GJB9001C.

性能参数/Performance Parameter

| 检测项目 Test Items | 测试方法 Test Method | 测试结果 Test Results |
|----------------------------------|---------------------|---|
| 燃烧性能测试 Flammability Test | GB/T 2408-2021 | 水平燃烧等级: HB HB I Horizontal Burning Rating: HB 垂直燃烧等级: V0 Vertical Burning Rating: V0 |
| 耐磨测试 Abrasion Resistance Test | ISO 6722-1:2006 | 4级 Grade 4 |

上述所有测试参数值均为典型值。产品测试报告详情请询销售代表。

All the above test parameter values are typical values. For specific product test reports, please consult your sales representative.

产品规格/Specifications

| 型号 Part No. | 参考折径 Reference Width (mm) | 适用范围 Applicable Range (mm) | 包装长度 Reel Length (m/reel) | 货号 Art. No. |
|----------------|---------------------------------|----------------------------------|---------------------------------|----------------|
| EX600250301 | 3 ± 1 | 1~5 | 1000 | PET-003 |
| EX600250601 | 6 ± 2 | 3~9 | 500 | PET-006 |
| EX600250801 | 8 ± 2 | 5~12 | 300 | PET-008 |
| EX600251001 | 10 ± 2 | 7~15 | 300 | PET-010 |
| EX600251201 | 12 ± 2 | 8~18 | 300 | PET-012 |
| EX600251401 | 14 ± 2 | 10~20 | 300 | PET-014 |
| EX600251601 | 16 ± 3 | 12~22 | 300 | PET-016 |
| EX600251901 | 19 ± 3 | 14~25 | 300 | PET-019 |
| EX600252501 | 25 ± 4 | 18~30 | 200 | PET-025 |
| EX600252801 | 28 ± 4 | 20~35 | 200 | PET-028 |
| EX600253201 | 32 ± 4 | 25~40 | 200 | PET-032 |
| EX600253801 | 38 ± 4 | 30~45 | 100 | PET-038 |
| EX600255001 | 50 ± 5 | 40~60 | 100 | PET-050 |
| EX600256401 | 64 ± 5 | 45~80 | 50 | PET-064 |

*可根据要求裁切固定长度/It can be cut to a fixed length as required.

*可根据要求订做其它尺寸/Other sizes can be customized upon request.

