



产品特点/ Product Features

- 工作温度-50℃~150℃
Working Temperature
- 紧密的编织结构
Tightly Woven Structure
- 轻便柔软
Lightweight & Soft
- 防尘耐污
Dustproof and Stain
Resistant

EX400 采用紧密编织结构，覆盖率高，能有效包裹线缆并提供防护。它兼具轻便柔软的特性且具备微扩张性，安装时能灵活适配不同线径的线缆。

EX400 features a tightly woven structure with high coverage, effectively enveloping cables and providing protection. It combines lightweight and flexible properties with slight expandability, allowing for flexible adaptation to cables of different diameters during installation.

产品应用/Applications

EX400 适用于线束，门锁杆，管道，软管及电缆组件。

EX400 is suitable for wire harnesses, door lock rods, pipes, hoses and cable assemblies.

我们的工厂已通过 ISO 9001、IATF 16949、ISO 14001、ISO 45001 和 军工 GJB9001C 认证。

Our manufacturing site has been certified by ISO 9001, IATF 16949, ISO 14001, ISO 45001 and military GJB9001C.

性能参数/Performance Parameter

检测项目 Test Items	测试方法 Test Method	测试结果 Test Results
热老化测试 Heat ageing test	175℃, 240小时 175℃, 240hours	无破损 No damage.

上述所有测试参数值均为典型值。产品测试报告请详询销售代表。

All the above test parameter values are typical values. For specific product test reports, please consult your sales representative.

产品规格/Specifications

型号 Part No.	参考折径 Reference Width (mm)	适用范围 Applicable Range (mm)	包装长度 Reel Length (m/reel)
EX4002004XX	4 ± 1	2~4	200
EX4002006XX	6 ± 1	5~7	100
EX4002007XX	7 ± 1	7~8	100
EX4002008XX	8 ± 1	8~10	100
EX4002010XX	10 ± 2	10~12	100
EX4002012XX	12 ± 2	12~14	100
EX4002014XX	14 ± 2	14~16	100
EX4002016XX	16 ± 2	16~18	100
EX4002018XX	18 ± 2	18~20	100
EX4002020XX	20 ± 2	20~23	100
EX4002035XX	25 ± 3	24~28	100

**XX"表示颜色, XX=01, 表示黑色; XX=08表示军绿色。

**XX" denotes the color: XX=01 indicates black; XX=08 indicates army green.

