



产品特点/ Product Features

- 工作温度-50℃~150℃
Working Temperature
- 可扩展性
Expandability
- 易于安装
Easy Installation
- 卓越阻燃性
Excellent Flame Retardancy
- 耐酸碱碱性
Acid and Alkali Resistance
- 出色的耐磨性
Excellent Abrasion Resistance
- 轻便透气的织物设计
Lightweight and Breathable Textile Design

EX300 采用 PET 与 PA 单丝混合编织，能扩展至其直径的数倍，易于安装，具有优异的耐磨性，耐化学腐蚀性。

EX300 is braided with a blend of PET and PA monofilaments that can expand to several times its diameter, is easy to install, and has excellent abrasion and chemical resistance.

产品应用/Applications

EX300 适用于汽车的软管管道和其他关键部件。

EX300 is suitable for hose ducts and other critical parts of automobiles.

我们的工厂已通过 ISO 9001、IATF 16949、ISO 14001、ISO 45001 和 军工 GJB9001C 认证。

Our manufacturing site has been certified by ISO 9001, IATF 16949, ISO 14001, ISO 45001 and military GJB9001C.

性能参数/Performance Parameter

检测项目 Test Items	测试方法 Test Method	测试结果 Test Results
燃烧性能测试 Flammability Test	FMVSS 302	符合 Pass
耐磨测试 Abrasion Resistance Test	ISO 6722-1:2006	6级 Grade 6

上述所有测试参数值均为典型值。产品测试报告请详询销售代表。

All the above test parameter values are typical values. For specific product test reports, please consult your sales representative.

产品规格/Specifications

型号 Part No.	参考折径 Reference Width (mm)	适用范围 Applicable Range (mm)	包装长度 Reel Length (m/reel)
EX300100601	6 ± 2	3~9	300
EX300100801	8 ± 2	5~12	300
EX300101001	10 ± 2	7~15	300
EX300101201	12 ± 2	8~18	200
EX300101401	14 ± 2	10~20	200
EX300101601	16 ± 3	12~22	200
EX300101901	19 ± 3	14~25	200
EX300102501	25 ± 3	18~30	200
EX300103201	32 ± 4	25~40	150
EX300103801	38 ± 4	30~45	100
EX300105001	50 ± 5	40~60	100

*可根据要求裁切固定长度/It can be cut to a fixed length as required.

*可根据要求订做其它尺寸/Other sizes can be customized upon request.

