



产品特点/ Product Features

- 工作温度-50℃~150℃
Working Temperature
- 轻巧柔韧
Lightweight and Flexible
- 易安装
Easy Installation
- 良好的扩充性
Good Expandability

EX601 是由 0.25mm 的 PET 单丝编织而成。该产品具有良好的扩展性和阻燃性。

EX601 is braided from 0.25mm PET monofilament. The product has good extensibility and flame retardancy.

产品应用/Applications

EX601 通常用于汽车低压线束和电子连接器线束。

EX601 is usually used for automotive low voltage wiring harnesses and electronic connector harnesses.

我们的工厂已通过 ISO 9001、IATF 16949、ISO 14001、ISO 45001 和 军工 GJB9001C 认证。

Our manufacturing site has been certified by ISO 9001, IATF 16949, ISO 14001, ISO 45001 and military GJB9001C.

性能参数/Performance Parameter

检测项目 Test Items	测试方法 Test Method	测试结果 Test Results
阻燃测试 Flame retardant test	GB/T 2408	水平燃烧等级 HB Horizontal Burning Rating: HB 垂直燃烧等级 V0 Vertical Burning Rating: V0

上述所有测试参数值均为典型值。产品测试报告请详询销售代表。

All the above test parameter values are typical values. For specific product test reports, please consult your sales representative.

产品规格/Specifications

型号 Part No.	参考折径 Reference Width (mm)	单丝线径 Monofilament Diameter (mm)	适用范围 Applicable Range (mm)	包装长度 Reel Length (m/reel)
EX601250301	3 ± 1	0.25	3~8	1000
EX601250401	4 ± 1	0.25	5~11	1000
EX601250601	6 ± 1	0.25	8~14	1000
EX601250801	8 ± 1	0.25	11~16	1000
EX601251001	10 ± 1	0.25	20~24	500
EX601251201	12 ± 1	0.25	25~30	500
EX601251501	15 ± 1	0.25	30~54	400

*可根据要求裁切固定长度/It can be cut to a fixed length as required.

*可根据要求订做其它尺寸/Other sizes can be customized upon request.

